

PRODUCT DESCRIPTION

Fiberglass flooring tissue products are the substrate material of plastic floor and decorative wallpaper. The floor and wallpaper made by this product have the property of good stability, smooth appearance, bright color and convenient laying. It is widely used for decoration materials for hospitals, schools, libraries and other public entertainment places, also hotels, shopping centers, conference halls, offices and residential buildings and other high-grade ground and wall.









F-DB40

CHARACTERISTICS

- Fiber Uniformly Dispersed
- Smooth Surface, Less Wool Yarn
- Easy to Coating PVC
- Stiff, Folding Resistance, not Easy to deformation
- Good Dimensional Stability

TECHNICAL DATA

Product code	Unit Weight	LOI	MD Tensile Strength	CD Tensile Strength	Thickness	Moisture Content
	g/m2	%	N/5CM	N/5CM	mm	%
F-DB25	25	≤25	≥ 80	≥50	0.2	≤ 1.0
F-DB0.3	35	≤30	≥ 150	≥70	0.30	≤ 1.0
F-DB40	40	≤30	≥180	≥80	0.35	≤ 1.0
F-DB45	45	≤30	≥ 200	≥90	0.35	≤ 1.0
F-DB50	50	≤30	≥250	≥100	0.40	≤ 1.0
Testing Basis	ISO3374	ISO1887	ISO3342	ISO4603	ISO 3344	ISO 3344
Paper core diam	eter: 152mm	•	•	•	•	

Remark: 1. Other specification can be customized according to customer' s demand.

2. The technical data above is for reference only

PACKING

Every roll in plastic film without pallet.

STORAGE

This product should be stored in a dry, ventilated and rainproof place, with temperatures from 5℃ to 35℃ and humidity between 35% and 65%. It is recommended to be kept in intact package when not used to avoid damp.

Address: No.20 Jiangjun Ave., Nanjing, P.R. China URL: www.fiberglassnonwoven.com E-mail: sales@njefg.com Version #: No.201911 Tel.: 0086 25 52270147 / 58321911 Fax: 0086 25 58321442 WhatsApp: 0086 18851651909